## IN THE CLAIMS

Please consider the claims as follows:

1. (Currently Amended) A luminaire comprising a housing suitable for accommodating at least one light source for emitting a light beam through a light-transmitting plate of the housing, eharacterized in that wherein a diffuse reflective coating is provided on an inner side of said housing, the diffuse reflective coating having a water-based solvent comprising at least 80% by weight of water, and the coating comprising at least 30% by weight of a binder based on a polymer having the following structural formula:

wherein  $R^1$  comprises an element chosen from the group Br, Cl, I, F, H, wherein  $R^2$  comprises an element chosen from the group Br, Cl, I, F, H, or an alkyl group, wherein  $R^3$  comprises an element chosen from the group Br, Cl, I, F, H, or COOCH<sub>3</sub>, and wherein  $R^4$  comprises an element chosen from the group Br, Cl, I, F, H, OH, or vinylether.

- 2. (Cancelled)
- 3. (Cancelled)
- 4. (Previously Presented) A luminaire according to claim 1, wherein the diffuse reflective coating is applied as a back reflector on the inner back surface of the housing.

- (Currently Amended) A luminaire according to claim 4, wherein the diffuse reflective coating reflects more than 90%, particularly more than 95% of normally incident light thereon.
- (Previously Presented) A luminaire according to claim 1, wherein the diffuse reflective coating is cross-linked with a polyisocyanate compound.
- 7. (Withdrawn) A luminaire comprising a housing suitable for accommodating at least one light source for emitting a light beam through a light-transmitting plate of the housing, characterized in that said housing is provided with a diffuse reflective coating having a binder on the basis of organically modified silane of the sol-gel type, wherein said diffuse reflective coating is applied as a diffuser on the light-transmitting plate.
- 8. (Withdrawn) A luminaire according to claim 7, wherein said organically modified silane has the following structural formula:

R<sup>I</sup>Si(OR<sup>II</sup>)<sub>3</sub>

wherein  $R^{\rm I}$  comprises an alkyl group or an aryl group and wherein  $R^{\rm II}$  comprises an alkyl group.

- (Previously Presented) A luminaire according to claim 1, wherein the diffuse reflective coating is applied as a diffuser on the light-transmitting plate.
- 10. (Currently Amended) A luminaire according to claim 9, wherein the diffuse reflective coating transmits more than 60 %, particularly more than 70 % of normally incident back light thereon.

- 11. (Previously Presented) A luminaire according to claim 9, wherein the diffuse reflective coating is provided with a layer that blocks ultraviolet light.
- 12. (Original) A luminaire according to claim 11, wherein said layer is applied on one side and/or both sides of the diffuse reflective coating and/or within the diffuse reflective coating.
- 13. (Currently Amended) A luminaire according to claim 11, wherein said layer comprises a metal oxide chosen from the group of ZnO, M<sub>2</sub>O<sub>3</sub> (M being B, Al, Sc, La or Y) and MO<sup>2</sup> MO<sub>2</sub> (M being Ce, Ge, Sn, Ti, Zr, or Hf) or a metal phosphate chosen from the group of M<sub>x</sub>(PO<sub>4</sub>)<sub>n</sub> and M<sub>x</sub>(PO<sub>3</sub>)<sub>n</sub> (M being an alkali metal, an earth alkali metal, Al, Sc, Y, La, Ti, Zr. or Hf).
- 14. (Previously Presented) A luminaire according to claim 1, wherein the diffuse reflective coating comprises calcium halophosphate, calcium pyrophosphate, BaSO<sub>4</sub>, MgO, YBO<sub>3</sub>, TiO<sub>2</sub>, or Al<sub>2</sub>O<sub>3</sub> particles.
- 15. (Previously Presented) Device with an LCD screen having a luminaire according to claim 1.
- (Previously Presented) Ceiling element or wall element having a luminaire according to claim